



SAFETY RAIL CO.
THE SAFEST



Architectural Series

SRC Accu-Fit Mobile Rail

The SRC Accu-Fit Mobile Safety Rail system is a non-penetrating, passive fall protection barrier system that protects workers from accidental falls. This system offers a continuous, uniform, vertical profile and a swept back railing profile that both enhances appearance and is often desirable by clients for use in high traffic areas in view of the public.



Features

- ⊗ Non-penetrating system
- ⊗ Modular design for unlimited configurations
- ⊗ No welding or drilling required for installation
- ⊗ Standard Finish Options: Powder-coated Safety Yellow & Galvanized
- ⊗ No intermediate counterweights required
- ⊗ American Welding Society Certified (AWS D1.1 & D1.3)
- ⊗ 100% Made in USA

Applications

The SRC Accu-Fit Mobile Rail system is designed especially for flat, membrane roof tops requiring OSHA-compliant fall protection or barrier guarding. Commonly used in industrial, commercial and work-site/construction environments as a permanent or temporary protection solution.

Minimum Requirements

- ✓ All rail segments along leading edge must begin and end with a 5' (152cm) return rail with base
- ✓ Designed for flat and low-sloped roofs, up to a 1:12 roof pitch (for steeper sloped roofs, guidance will be provided)
- ✓ 18" base offset from leading edge when no parapet is present


Accu-Fit Mobile Rail

PRODUCT SPECIFICATIONS




Dimensions & Length Options


**Assembled Height*



Traditional Series



Architectural Series



**Railing length options: 8' max in the State of California*



Diameter Options

1¼"	Schedule 40
1½"	Schedule 40

Interlocking Pin System



Finish Options

Safety Yellow


Galvanized

Custom Colors

Product Specifications

Tested for 200 lb (90.7kg) force in a downward or outward direction
Assembled height: 42" (107cm) top rail, 21" (53cm) mid rail or 19" (48cm) mid rail
Mounting base weight: 104 lbs (45.8kg)/ea
1¼" or 1½" SCH 40 galvanized pipe

Positive locking pin system
EPDM base pads come pre-installed on all bases
SRC Safety Pins: 1010 carbon steel and zinc plated
100% Made in USA
American Welding Society Certified (AWS D1.1 & D1.3)



Traditional Series

Installation

- ☑ Safety Rail Co. provided project specific product install plan available
- ☑ No welding or drilling required
- ☑ 21' pipe lengths; cut pipe to length as needed
- ☑ Mobile, multi-location capability
- ☑ Complete installation guidelines available electronically
- ☑ Base-mover dolly available upon request

Compliance

Compliant with OSHA standards for guardrails: (29 CFR 1910.29 & 29 CFR 1926.502)
Independently tested by a nationally accredited engineering lab
– documentation available upon request